

Putzmeister

Boom	Reach	Gross Weight	Pedestal	Support	Support	Max. support leg forces dyn. (or tire force if no support)	
				Front	Rear	Front	Rear
M31-5 MZR	82 ft.	68,000 lbs.	TRDI80	TB2221	SB3900	210 kN (47210 lbf)	210 kN (47210 lbf)
M32-4 Z	85 ft.	68,000 lbs.	TRDI65	TB2120	SB3800	140 kN (31473 lbf)	155 kN (34845 lbf)
M36-4 Z	96 ft.	70,000 lbs.	TRDI65	TB2120	SB3800	175 kN (39342 lbf)	170 kN (38218 lbf)
M38-5 RZ	107 ft.	70,000 lbs.	TRDI80	TB2576	SB4260	195 kN (43838 lbf)	210 kN (47210 lbf)
M42-5 RZ	120 ft.	80,000 lbs.	TRDI110	TB3405	SB4600	240 kN (53954 lbf)	225 kN (50582 lbf)
M47-5 RZ	140 ft.	80,000 lbs.	TRDI130	TB2184	SB5300	245 kN (55078 lbf)	250 kN (56202 lbf)
M56-5 RZ	158 ft.	100,300 lbs.	TRDI210	TB2292	SB7400	310 kN (69691 lbf)	300 kN (62947 lbf)

Schwing

Boom	Reach	Gross Weight (lbs)	Front Outrigger Spread		Rear Outrigger Spread		Front to Rear Outrigger Spread		Maximum Front Outrigger		Maximum Rear Outrigger Load	
			(in)	(mm)	(in)	(mm)	(in)	(mm)	(lbs)	(kN)	(lbs)	(kN)
KVM 32	85 ft.	68,000	278	7061	192	4877	271	6883	30,430	135	22,930	102
S 58 SX	175 ft.	110,250	350	8890	493	12522	453	11506	78,680	350	83,176	370